

ELECTRONICS X3 PRO Platform | X3 PRO Sensor Pack

X3 PRO Platform



X3 PRO Sensor Pack



PRODUCT DESCRIPTION		
The X3 PRO Platform provides four data ports, control signals, communication relay functionality, electrical isolation and power for the sensor system.		
FEATURES		
Display Functionality	LED: green-power on, amber-malfunction	
Sensor Cell Capacity	256x256	
Sensor Ports	4	
POWER		
External Power Supply	Input: 100-240 VAC, 47-63Hz, 1.35 A Output: 12 VDC, 3.75 A	
Power Consumption	1 W	
PHYSICAL CHARACTERISTICS		
Length	4.5"	11.4cm
Width	3.5"	8.9cm
Height	0.9"	2.3cm
Weight	4.8oz	135g
ENVIRONMENT		
Operating Range (Temp.)	10°C to 40°C	
Ambient Humidity	80% for temperatures up to 31°C and decreasing linearly to 50% at 40°C	
USB Port		
USB Input	USB 2.0, Full Speed	
USB Cable (sold separate)	185cm length	

PRODUCT DESCRIPTION		
The X3 PRO Sensor Pack contains the sensing electronics of the system including one communication port.		
FEATURES		
Display Functionality	LED: green-power on, amber-malfunction	
Sensor Cell Capacity	64x64	
Sampling Rate	112,000 sensels/sec	
Sampling Resolution	16 bit	
Min Cell Measurement Time	35 µsec	
POWER		
Power Consumption	2 W	
PHYSICAL CHARACTERISTICS		
Length	3.9"	9.8cm
Width	2.5"	6.4cm
Height	0.7"	1.8cm
Weight	6.3oz	180g
Cable Length	78"	198.1cm
ENVIRONMENT		
Operating Range (Temp.)	10°C to 40°C	
Ambient Humidity	80% for temperatures up to 31°C and decreasing linearly to 50% at 40°C	